


SIRIUS 3SE5, 3SE2 Mechanical Safety Switches

With Separate Actuator

Accessories

Selection and ordering data

Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Actuators for 3SE51, 3SE52						
 3SE5000-0AV01	Standard actuators					
	Length 75.6 mm					
	▶ 3SE5000-0AV01					
				1	1 unit	41K
 3SE5000-0AV02	With vertical fixing, length 53 mm					
	B	3SE5000-0AV02		1	1 unit	41K
 3SE5000-0AV03	With transverse fixing, length 47 mm					
	B	3SE5000-0AV03		1	1 unit	41K
 3SE5000-0AW11	With transverse fixing, plastic¹⁾ Length 40 mm					
	B	3SE5000-0AW11		1	1 unit	41K
 3SE5000-0AV06	Radius actuators, length 51 mm					
	Direction of approach from the left					
	A	3SE5000-0AV04		1	1 unit	41K
	Direction of approach from the right					
	▶	3SE5000-0AV06		1	1 unit	41K
 3SE5000-0AV05-1AA6	Universal radius actuators					
	Length 77 mm					
	B	3SE5000-0AV05		1	1 unit	41K
	Length 77 mm, tab rotated 90°					
	B	3SE5000-0AV05-1AA6		1	1 unit	41K
 3SE5000-0AV07	Universal radius actuators, heavy duty					
	Length 67 mm					
	A	3SE5000-0AV07-1AK2		1	1 unit	41K
	Length 77 mm					
	B	3SE5000-0AV07		1	1 unit	41K
Optional accessories for 3SE5						
 3SE5000-0AV08-1AA2	Protective caps made of black rubber for the actuator head, to protect the actuator openings from contamination (Only for enclosure width 40 or 56 mm)					
	C	3SE5000-0AV08-1AA2		1	1 unit	41K
 3SE5000-0AV08-1AA3	Blocking inserts , high-grade steel, for actuator head, for up to eight padlocks					
	B	3SE5000-0AV08-1AA3		1	1 unit	41K
Connections for 3SE5, 3SE2						
 3SY3127	Connector sockets (4-pole), M12, fixed for M20 × 1.5					
	B	3SY3127		1	1 unit	41K
	For max. 250 V, 4 A					
	With 0.25 mm ² connecting cable, plastic, degree of protection IP67, ambient temperature –40 to +85 °C					
	Connector sockets (5-pole), M12, fixed for M20 × 1.5					
	B	3SY3128		1	1 unit	41K
	For max. 125 V, 4 A					
	With 0.25 mm ² connecting cable, plastic, degree of protection IP67, ambient temperature –40 to +85 °C					
 3SX9926	Cable glands M20 × 1.5					
	A	3SX9926		1	1 unit	41K
Plastic						

¹⁾ Not suitable for safety switches with interlocking.