


Version	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
---------	----	-------------	--------------	-------------------	-----	----

Accessories

	AS-Interface sealing caps				▶ A	3RK1901-1KA00 3RK1901-1PN00	100	10 units	42C
3RK1901-1KA00	• For free M12 sockets • For free M8 sockets								
	AS-Interface compact distributors, for AS-Interface flat cable				A	3RK1901-1NN10	1	1 unit	42C
3RK1901-1PN00	Current carrying capacity up to 8 A								
	AS-Interface M12 feeders								
3RK1901-1NN10	• Degree of protection IP67 • Current carrying capacity up to 2 A								
	For flat cable	For	Cable length	Cable end in feeder	▶	3RX9801-0AA00	1	1 unit	42C
3RX9801-0AA00	AS-i	M12 socket	--	Available					
	AS-Interface M12 feeders								
3RK1901-1NR10	• Degree of protection IP67/IP68/IP69K • Current carrying capacity up to 4 A								
	For flat cable	For	Cable length	Cable end in feeder	A	3RK1901-1NR10 3RK1901-1NR11	1	1 unit	42C
3RK1901-1NR11	AS-i	M12 socket	--	Not available					
	AS-i	M12 cable box	1 m	Not available	A	3RK1901-1NR11	1	1 unit	42C
	AS-i	M12 cable box	2 m	Not available	A	3RK1901-1NR12	1	1 unit	42C
3RK1901-1NR11	AS-i/U _{aux}	M12 socket	--	Not available	A	3RK1901-1NR20	1	1 unit	42C
	AS-i/U _{aux}	M12 cable box	1 m	Not available	A	3RK1901-1NR21	1	1 unit	42C
3RK1901-1NR11	AS-i/U _{aux}	M12 cable box	2 m	Not available	A	3RK1901-1NR22	1	1 unit	42C
	AS-Interface M12 feeders, 4-fold								
3RK1901-1NR04	Current carrying capacity up to 4 A								
	For flat cable	For	Cable length	Cable end in feeder	A	3RK1901-1NR04	1	1 unit	42C
3RK1901-1NR04	AS-i/U _{aux}	4-fold M12 socket, delivery includes mounting plate (for wall and standard rail mounting)	--	Not available					
	M12 T distributors				C	3RK1901-1TR00	1	1 unit	42C
3RK1901-1TR00	• IP68 • 1 x M12 plug • 2 x M12 box								
	M12 Y-shaped coupler plugs				A	6ES7194-1KA01-0XA0	1	1 unit	250
6ES7194-1KA01-0XA0	For connection of two sensors to one M12 socket with Y assignment								
	M12 connecting cables				C	3RK1902-4PB15-3AA0	1	1 unit	42D
3RK1902-4PB15-3AA0	• 3-pole • For addressing AS-i slaves with M12 bus connection • Cable length 1.5 m								