

Product datasheet

Characteristics

CHOM2175SB

CANADIAN CHOM SECONDARY SURGE ARRESTER



Main

Product or component type	Secondary surge arrester
Range of product	Homeline Surge Breaker

Complementary

Surge current	22.5 kA
[Ue] rated operational voltage	120/240 V AC
Network number of phases	1 phase
Wiring configuration	3-wire
[Uc] maximum continuous operating voltage	150 V 300 V
[In] rated current	5 kA
Short-circuit protection	22 kA
Local signalling	1 LED, green = normal operation
Product destination	Load center
Height	3.7 in
Width	2 in
Depth	2.6 in

Environment

NEMA degree of protection	NEMA 1
ambient air temperature for operation	65 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.