

Product datasheet

Characteristics

2510KR2H

Manual Switch - NEMA 7&9 - 3P - Toggle Operated -
No Indicator - 600VAC



Main

Product or component type	Single Unit Manual Switch
Range of product	K

Complementary

[In] rated current	20 A
Cable entry	0.75 NPT (top and bottom)
Motor power hp	2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC
[Ue] rated operational voltage	600 V AC 230 V DC
Poles description	3P
Control type	Toggle
Network number of phases	3 phases
Local signalling	No indicator
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 10 (copper)
Height	6.36 in
Width	3.95 in
Depth	4.35 in

Environment

product certifications	CE UL listed file E58760 CCN NPXZ CSA LR26817 class 3218 04
NEMA degree of protection	NEMA 3R/7/9 cast aluminium standard size

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.